

Granville Hypalube LL FS 5W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

PRODUCT DESCRIPTION

Hypalube LL 5W/30 is formulated primarily to meet the GM longlife requirements using the most advanced additive technology to produce a fuel efficient engine oil that has excellent high and low temperature performance and exceptional long term anti wear characteristics. Suitable for use in petrol & diesel engines where specified including Vauxhall, Opel and Saab.

RECOMMENDED FOR USE BY GRANVILLE FOR THE FOLLOWING MANUFACTURER'S SPECIFICATIONS

ACEA: A3/B4
 API: SL/CF
 BMW: LL-01 & LL-98
 GM: LL-A-025 & LL-B-025
 MB: 229.3
 Opel: B-040-2095 & B-040-2098
 VW: 505.00 & 502.00

PRODUCT BENEFITS

- * Ensures lubricant performance over extended drain intervals
- * Excellent high & low temperature performance
- * Outstanding fuel efficiency
- * Effective environmental protection

PRODUCT USAGE

For engines where this specification lubricant is required.

DIRECTIONS FOR USE

As recommended by the engine manufacturer



* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
1 Litre	1121	5020618011217
5 Litre	1122	5020618011224
20 Litre	1123	5020618011231
199 Litre	1126	5020618011262



Granville Hypalube LL FS 5W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

STORAGE INSTRUCTIONS

Keep sealed in a cool, dry place

SHELF LIFE

5 years from date of manufacture

Appearance	: Amber liquid
Odour	: Characteristic
Solubility	: Insoluble in water
Percentage of Biodiesel	: Nil

Test	Method	Unit	Min.	Max.	Typical
Viscosity, Kinematic 100°C	ASTM D445	mm ² /s	9.3	<12.5	
Viscosity, CCS -30°C	ASTM D4684	mPa.s		<6600	
Total Base Number	ASTM D2896	mg KOH/g	10		
HTHS Viscosity	ASTM D4683	mPa.s	>3.5		
NOACK Volatility	ASTM D5800	%		10	
Pour Point	ASTM D97	°c		-27	

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

